

Bromine Quick-Start Guide

Pro Supplies Kit - KT1004

1. Clean Tub & New or Clean Filter(s)



Start with an empty, clean tub and new or clean filter cartridge(s).
(Use [Spa System Flush](#) when transitioning from any previous sanitizer system.)

2. Fill spa and circulate water with jets



Fill spa with fresh water. After full, jets must be on to circulate the water while adding chemicals to effectively distribute throughout entire tub.

3. Test water



Test water with [Bromine 4-in-1 test strips](#); adjust if necessary.

Bromine: 3.0 - 5.0 ppm **Total Alkalinity (TA):** 80 - 120 ppm **pH:** 7.2 - 7.6 **Water Hardness:** 150 - 300 ppm

4. Add natural clarifier



Add 1 oz. of [natural clarifier](#) per 500 gallons of spa water, weekly.

5. Add Metal Free



Add [Metal Free stain/metal preventer](#) per label instructions.

6. Shock water with Oxy-Spa



Shock spa water at initial fill and weekly. Add 1.5 - 2 oz of non-chlorine [MPS Oxy-Spa](#) per 500 gallons.
(2 oz. = approx 1 ½ tablespoons)

7. Add Granular Bromide Booster



Add 2.5 oz per 500 gallons of [Granular Bromide Booster](#) to establish an immediate bromide reserve or bank.

8. Add Bromine Tablets to Float



Add 3 - 4 [Bromine Tablets](#) to [Float \(brominator\)](#). Open brominator to the 2 or 3 mark and lock down. Hold brominator underwater to remove air bubbles, and allow to float to surface. Adjust release opening, more or less, as experience dictates over time to maintain bromine at 3 - 5 ppm. Add tablets as depleted.

9. Circulate water for 1 - 2 hours and retest



Allow water to circulate to equilibrate spa chemicals for an hour or two (or overnight) then retest; adjust if necessary.

10. Place ZorbO in spa



Place and keep [ZorbO](#) in spa to absorb oil scum.
Rinse out every 1 - 2 weeks and replace every 3 - 6 months.
After each spa use, add 1 - 2 tablespoons [Oxy-Spa](#).
Follow label instructions according to your spa's capacity guidelines.

SpaDepot[®]
(800) 823-3638 .com
Mon-Fri 6 AM - 5 PM PST